

REMARKS

The present invention is a method of logging events in a multimedia integrated receiver decoder, a system for logging events in a multimedia integrated receiver decoder, a computer program product directly loadable into the internal memory of a multimedia integrated receiver decoder, a multimedia integrated receiver decoder and a system for logging events in a multimedia integrated receiver decoder. A method of logging events in a multimedia integrated receiver decoder 40 in accordance with the invention includes providing a trigger 100; transmitting the trigger to the integrated receiver decoder in a data stream together with an event to be monitored; if the integrated receiver decoder is tuned to the data stream, storing the trigger and transmitting the stored trigger information from the integrated receiver decoder without user identification information. The transmission of the trigger without user identification information's described on page 7, lines 26-28, of the specification.

Claims 1-4 and 7-11 stand rejected under 35 U.S.C. §102(e) as being anticipated by United States Patent 5,872,588 (Aras et al). This ground of rejection is traversed for the following reasons.

Independent claims 12, 22, 23 and 24, which respectively correspond to claims 1 and 2, 9 and 10, recite, *inter alia*, the transmitting of the stored trigger information from the integrated receiver decoder without user identification information. This subject matter is not taught by Aras et al and is not rendered obvious therefrom. This subject matter satisfies the need for personal privacy involving the processing of logging events so as to provide useful information of

when the integrated receiver decoder is tuned to the data stream by storing a trigger and further reporting back to a data gathering entity information regarding the operation of the integrated receiver decoder pertaining to the received data stream detected by the receiver decoder without revealing the consumer of the multimedia data stream.

Aras et al teach a method and apparatus for monitoring audio visual materials presented to a subscriber which operates to monitor a home station's decoding of a transmitted data stream so as to create a profile of the subscriber to individual or more directly target the marketing of new interactive television products and/or product enforcements. See column 6, lines 31-44, and further column 7, lines 6-28, wherein it is described that each subscriber activity is recorded in either the home station or an interactive content providing equipment to facilitate collection of information correlated with the purchasing behavior of the subscriber which is resold to marketers of services and advertising agencies. In other words, Aras et al would not contemplate maintaining subscriber privacy as reflected by the subject matter of claims 12, 22, 23, and 24.

Moreover, there is no basis in the record why a person of ordinary skill in the art would be led to modify the teachings of Aras et al to arrive at the subject matter of newly submitted claims 12-24.

Claim 19, which recites, *inter alia*, that the single event is a commercial, is supported by page 7, line 28 through page 8. line 2.

Newly submitted claims 20 and 21 are supported by page 9, lines 21-23, of the specification. .

Newly submitted independent claims 25 and 27-29 respectively recite a method of logging events in a multimedia integrated receiver decoder, a multimedia integrated receiver decoder, a system for logging events in a multimedia integrated receiver decoder and a computer program product directly loadable into the internal memory of a multimedia integrated receiver decoder in which, *inter alia*, triggers are provided to an integrated receiver decoder in combination with an event to be monitored and a channel identifier is stored identifying the channel presently tuned to together with a time stamp if the integrated receiver decoder is tuned to the data stream.

Claim 6 was rejected under 35 U.S.C. §103 as being unpatentable over Aras et al in view of United States Patent 4,258,386 (Cheung). This ground of rejection is traversed with respect to newly submitted claims 25-29.

Aras et al is properly acknowledged as not teaching the channel identifier and time stamp.

Cheung teaches a television audience measuring system. It is submitted that the Examiner has not demonstrated any motivation for combining Cheung with Aras et al as discussed in the rejection of claim 6. Accordingly, it is submitted that the subject matter of claims 25, 27, 28 and 29 is not obvious based upon a lack of motivation being demonstrated to combine Aras et al and Cheung.

Newly submitted claim 26 further limits claim 25 in reciting that the trigger comprises only a command for storing said channel identifier and time stamp. It is submitted that there is no teaching in either Aras et al or Cheung which would render obvious the subject matter of claim 26.

Moreover, newly submitted claims 30-33 further respectively limit claims 25, 27, 28 and 29 in reciting that the trigger is provided without an identification of the trigger which covers the subject matter of page 8, lines 3-16. There is no basis in the record why a person of ordinary skill in the art would be led to modify the teachings of Aras et al and Cheung to arrive at the subject matter of newly submitted claims 30-33.


In view of the foregoing amendments and remarks, it is submitted that each of the claims in the application is in condition for allowance.

Accordingly, early allowance thereof is respectfully requested.

To the extent necessary, Applicants petition for an extension of time under 37 C.F.R. §1.136. Please charge any shortage in fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account No. 01-2135 (1124.40655X00) and please credit any excess fees to such Deposit Account.

Respectfully submitted,

ANTONELLI, TERRY, STOUT & KRAUS, LLP



Donald E. Stout
Registration No. 26,422
(703) 312-6600

Attachments

DES:dlh

1124.40655X00LOGGING OF EVENTSBACKGROUNDFIELD OF INVENTIONField of Invention

[0001] The present invention relates generally to logging of events in an Integrated Receiver Decoder, such as a multimedia terminal.

BACKGROUNDDescription of the Prior Art

[0002] Interactive television systems capable of two-way communication between computer systems operating as information service providers and networked Integrated Receiver Decoders (IRDs) are becoming increasingly popular. Such systems open up ~~for~~ new services and features for television users as well as for operators. A standard developed by the Project on Digital Video Broadcasting is the so-called Digital Video Broadcasting standard or simply DVB standard. Its main intent is to reap the benefits of ~~technical standardisation~~ standardization. For more information regarding the DVB standard, reference is made to the publication "Digital Television MPEG 1 MPEG 2 And principles of the DVB System", H Benoit, ISBN 0-471-23810-4, or to the DVB Home Page on the Internet: <http://www.dvb.org>, which are hereby incorporated by reference.

[0003] With the power of today's set-top boxes and other IRDs it is possible to ~~analyse~~ analyze the

[0003] ~~_____~~ With the power of today's set-top boxes and other IRDs it is possible to ~~analyse~~ analyze the ~~behaviour~~ behavior of television viewers by letting the IRD track the users channel switches. This is done by constantly logging the channel selection of the IRD and to send this information on a back channel to the operator system, wherein the information is used to evaluate the popularity of different television ~~programmes~~ programs etc. Unfortunately, this information collection can have the effect of disturbing the integrity of the users, giving them a feeling of being monitored. Another drawback is that the amount of log data grows very quickly as all channel switches are saved together with a time stamp over a relatively long period of time.

SUMMARY OF THE INVENTION

[0004] ~~_____~~ ~~An object of the~~ The present invention is ~~to provide a~~ method, a multimedia integrated receiver decoder and a system for logging the ~~behaviour~~ behavior of a multimedia user as well as a computer program product wherein the above mentioned drawbacks are eliminated or at least mitigated.

[0005] ~~_____~~ The invention is based on the ~~realisation~~ realization that not all channel switches of a user have to be logged. Thus, instead of logging event selection continuously, the answer to the question "is this event viewed now?" is logged.

[0006] ~~_____~~ ~~According to a~~ A first aspect of the invention ~~there is provided a method as defined in claim 1.~~

[0007] ~~According to a~~ A second aspect of the invention ~~there is provided a multimedia integrated receiver decoder as defined in claim 9.~~

[0008] ~~According to a~~ A third aspect of the invention ~~there is provided a system as defined in claim 10.~~

[0009] ~~According to a~~ A fourth aspect of the invention ~~there is provided a computer program product as defined in claim 11.~~

[0010] By using the method, the multimedia terminal, the system and the computer program product according to the invention the above ~~objectives are~~ subject matter is attained. Thus, the user gets less feeling of being watched. A further advantage is that the operator gets a smaller data set, which is also easier to transfer and to analyse.

BRIEF DESCRIPTION OF DRAWINGS

[0011] The invention is now described, by way of example, with reference to the accompanying drawings, in which:

[0012] FIG. 1 is an overall diagram of a communication system embodying the invention 7i

[0013] FIG. 2 is conceptual model of a user equipment utilising a DVB (MPEG-2) baseband processor for receiving information 7i and

[0014] FIG. 3 shows the general structure of a trigger used with the inventive method.

[0016] The backbone of a communication system for multimedia applications will now be briefly discussed with reference to ~~figure~~ Fig. 1. The backbone of the system comprises a number of communication paths 30, one of which is shown in ~~figure~~ Fig. 1. The transmission medium supports high-speed transmission of digital information, such as audio (A), video (V) and data (D). A number of users are connected to the backbone, of which a first baseband processor user 10 functions as a transmitter of information, ~~i.e. that is,~~ an operator, and a second user 40 functions as a receiver of multimedia information, such as a subscriber of television ~~programmes~~ programs.

[0017] A method covered by a standard, such as MPE, Multiprotocol Encapsulation, could be used to send the information to the receiver 40 through receiver equipment at the user, which will now be discussed with reference to ~~figure~~ Fig. 2. A transport stream arriving from the transmission medium is received at an input 41 and is first demultiplexed in a Transport Demultiplexer 42, splitting the information into several ~~programme~~ program streams comprising related elementary streams, four of which are shown as an example. The exemplary streams comprise a video stream V1, an audio stream A1 and two data streams D1.1, D1.2. This information results in a TV ~~programme~~ program, for example.

[0018] The video and audio streams are directed to a video and audio decoder 44, wherein the signals are decoded. The decoded audio and video signals are

[0018] The video and audio streams are directed to a video and audio decoder 44, wherein the signals are decoded. The decoded audio and video signals are ~~synchronised~~ synchronized in the decoder 44 by means of a so-called time stamp or PTS.

[0019] The decoded signals are input to a digital to ~~analogue~~ analog (D/A) converter 46, wherein the digital information is converted to ~~analogue~~ analog form useable by a TV encoder, such as a PAL encoder 48. The encoder 48 supplies the encoded information through an output 61 and to a presentation unit, in this case a TV set 60, on which the information is displayed.

[0020] The data information can comprise several kinds of information, some of which are user defined. In the present invention, the data stream is used to supply so-called triggers to the IRD 40. The triggers are explained in more detail below.

[0021] In order to keep track of time, the receiver 40 also comprises a clock reference 50. This clock is adjusted in accordance with timing signals sent by the transmitting processor 10, ~~e.g.~~ for example, the Service Provider. The time values of the clock 50 correspond to the PTS values of the incoming information.

[0022] The operation of the IRD 40 is controlled by means of software 70 run on suitable processor hardware (not shown). Thus, the software is stored in memory and is run either on request by the user or in response to some event.

[0023] The IRD also comprises a modem 90 providing a back channel to the operator 10, for example. Thus the modem is connected to some kind of communication medium, such as a telephone line. By means of the modem connection, data information generated and stored in the IRD 40 can be sent from the IRD through a modem output 91.

[0024] The inventive logging procedure will now be described in detail, partly with reference to ~~figure~~ Fig. 3. First the operator 10 determines which events, ~~e.g. for example~~, television ~~programmes~~ programs and commercials, that are to be logged. For example, an advertiser is interested in knowing the response to a specific TV commercial, ~~i.e. that is~~, are television viewers actually watching the commercials? Triggers for that commercial is then created by hardware and software (not shown) in the transmitter 10.

[0025] Triggers created at the operator 40 are then sent with the data stream to the user 40 at the time the event associated with the trigger is sent. The software 70 continuously monitors the incoming data stream to which the IRD is currently tuned to and every trigger found in the stream is stored in a trigger memory 80. The structure of a preferred trigger 100 is shown in ~~figure~~ Fig. 3 and the trigger comprises a header 101 indicating that it is a trigger and a field 102 containing a unique trigger identification ID.

[0026] The trigger ID 102 can be for example a numerical value, wherein different operators have different number series to ensure that each trigger has a unique ID. However, the IDs have to be unique only

[0027] If the IRD is tuned to the channel in which the event to be monitored was sent, the software 70 identifies the trigger header 101 in the data stream. After having identified the information as a trigger, the software extracts the trigger ID 102 from the stream. The trigger ID is preferably stored as a file in a non-volatile memory, such as a hard disk, in a trigger log 80. The trigger log contains a list of trigger IDs and nothing more, which provides for a compact information occupying a limited amount of storage space.

[0028] Thus, there is no selectivity in the IRD 40, i.e., every time a trigger 100 is identified, its associated ID 102 is stored in the trigger log. This provides for a simple yet reliable monitoring of channel selection. However, the inventive monitoring method does not provide a complete information of which channel is selected at every moment; it only provides an answer to the question: "is the IRD currently tuned to this channel?" This question has a much lesser impact on the integrity of the user.

[0029] At irregular or regular intervals, such as once every week or month, the trigger log 80 is sent to the operator 10 for evaluation. This transmittal of the trigger log can be either time driven in the case of regular intervals or it can be initiated either by the operator or the user, e.g. for example, by selecting a menu option.

[0030] The trigger log 80 can be sent with an accompanying user identification so that the receiver of the information will know who has created this

[0030] The trigger log 80 can be sent with an accompanying user identification so that the receiver of the information will know who has created this particular trigger log. Alternatively, to lessen the integrity disturbance, the trigger log 80 is sent without user identification. In that way, the receiver of the trigger log 80 will not know the preferences for a specific user but will nevertheless be able to evaluate the general interest for a TV commercial, for example.

[0031] In an alternative embodiment of the method according to the invention, the unique trigger ID 102 is omitted from the trigger 100. Instead, only the trigger header 101 is sent in the data stream. The software 70 monitors the stream as in the first embodiment and when a trigger header is found, the software 70 adds information to the trigger log 80. However, in this second embodiment, the software itself provides the information to be stored in the trigger log 80, namely a channel ID and a time stamp obtained from the clock 50. These two information items together define the monitored event. As in the first embodiment, the trigger log is later sent to the operator for further evaluation.

[0032] In order to use the inventive method, some kind of agreement between operator and user is probably needed. This can be in the form of a written agreement, wherein the user permits the operator to use the method. This agreement could be connected to some kind of fee reduction for using the operator's services,

example, once every week, a text like "Please confirm transmittal of information to operator: YES/NO". By pressing the YES button on his/her remote control, the user agrees to the use of the inventive method and initiates transmittal of the trigger log 80 via the modem connection 90.

[0034] With the inventive method, limited amounts of data are generated. This is an advantage when equipment with relatively limited bandwidth, such as the modem 90, is used for transmitting the data back to the operator.

[0035] Preferred embodiments of the invention have been described. The person skilled in the art ~~realises~~ realizes that these can be varied within the scope of the appended claims. Thus, a specific multimedia standard has been described, but any form of communication system using a data stream is feasible.

[0036] In the preferred embodiments, the trigger log 80 is transmitted by modem to an operator 40. However, this trigger log can be sent in any convenient way and to other parties than the operator as well, such as directly to an advertiser having a TV commercial monitored. In that way, the advertiser gets the requested feedback much quicker and easier than if another party first receives the information.

[0037] Optionally there can be "start" and "stop" triggers, by means of which it can be checked whether an entire event has been viewed. This solves the problem when a trigger is activated at the beginning of ~~a programme~~ program, for example. If the user chooses

[0037]_____ Optionally there can be "start" and "stop" triggers, by means of which it can be checked whether an entire event has been viewed. This solves the problem when a trigger is activated at the beginning of a ~~programme~~program, for example. If the user chooses to switch to a different channel after a few minutes, the trigger indicates that the ~~programme~~program has been watched even though only a part of it was actually watched. Thus, if both the start trigger sent at the beginning of the event and the stop trigger sent at the end of the event are logged, the event can be considered to have been watched.

[0038]_____ A back channel provided by means of a modem connection has been described. It is obvious that this back channel can be provided by any suitable means known to the person skilled in the art.

[0039]_____ The exact content of the trigger log 80 can of course also vary.

ABSTRACT

A method of logging events in a multimedia integrated receiver decoder comprises the following steps: providing a trigger, transmitting said trigger to said integrated receiver decoder in a data stream together with an event to be monitored, and if said integrated receiver decoder is tuned to said data stream, storing said trigger. This provides for a method wherein the amount of data required to be stored and transmitted is kept to a minimum and wherein the integrity of a user is maintained.

~~(FIG. 2)~~

